

# **Кондуктометры – термометры стационарные DELTA ОНМ HD3406.2**

## **Технические характеристики**

Архангельск (8182)63-90-72  
Астана (7172)727-132  
Астрахань (8512)99-46-04  
Барнаул (3852)73-04-60  
Белгород (4722)40-23-64  
Брянск (4832)59-03-52  
Владивосток (423)249-28-31  
Волгоград (844)278-03-48  
Вологда (8172)26-41-59  
Воронеж (473)204-51-73  
Екатеринбург (343)384-55-89  
Иваново (4932)77-34-06

Ижевск (3412)26-03-58  
Иркутск (395)279-98-46  
Казань (843)206-01-48  
Калининград (4012)72-03-81  
Калуга (4842)92-23-67  
Кемерово (3842)65-04-62  
Киров (8332)68-02-04  
Краснодар (861)203-40-90  
Красноярск (391)204-63-61  
Курск (4712)77-13-04  
Липецк (4742)52-20-81  
Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13  
Москва (495)268-04-70  
Мурманск (8152)59-64-93  
Набережные Челны (8552)20-53-41  
Нижний Новгород (831)429-08-12  
Новокузнецк (3843)20-46-81  
Новосибирск (383)227-86-73  
Омск (3812)21-46-40  
Орел (4862)44-53-42  
Оренбург (3532)37-68-04  
Пенза (8412)22-31-16  
Казахстан (772)734-952-31

Пермь (342)205-81-47  
Ростов-на-Дону (863)308-18-15  
Рязань (4912)46-61-64  
Самара (846)206-03-16  
Санкт-Петербург (812)309-46-40  
Саратов (845)249-38-78  
Севастополь (8692)22-31-93  
Симферополь (3652)67-13-56  
Смоленск (4812)29-41-54  
Сочи (862)225-72-31  
Ставрополь (8652)20-65-13  
Таджикистан (992)427-82-92-69

Сургут (3462)77-98-35  
Тверь (4822)63-31-35  
Томск (3822)98-41-53  
Тула (4872)74-02-29  
Тюмень (3452)66-21-18  
Ульяновск (8422)24-23-59  
Уфа (347)229-48-12  
Хабаровск (4212)92-98-04  
Челябинск (351)202-03-61  
Череповец (8202)49-02-64  
Ярославль (4852)69-52-93

**Technical characteristics HD3406.2**  
 $\chi$ ,  $\Omega$ , TDS, NaCl, °C/°F measurement

## HD3406.2



## HD3406.2

### BENCH-TOP CONDUCTIVITY METER

The HD3406.2 is a bench top instrument for electrochemical measures: **conductivity and temperature**.

The displayed data can be stored (**datalogger**) and can be transferred to PC or serial printer thanks to the multi-standard serial port RS232C and USB2.0 and software DeltaLog9 (Vers.2.0 and subsequent ones). The storing and printing parameters can be set from menu.

The HD3406.2 measures **conductivity, resistivity in liquids, total dissolved solids (TDS) and salinity** using combined 4-ring and 2-ring conductivity/temperature probes. Temperature is measured by Pt100 or Pt1000 immersion, penetration or contact probes.

The probe calibration can be performed automatically in one or more of the 147µS, 1413µS, 12880µS or 111800µS/cm conductivity calibration solutions.

The display shows continually the temperature in °C or °F and one selectable parameter according to the connected probe type, i.e. in case of conductivity probe it is possible to select between  $\chi$  or  $\Omega$  or TDS or NaCl.

Other functions of this instrument include: Max, Min and Avg function, the Auto-HOLD function, the automatic turning off which can also be excluded.

The instruments have **IP66 protection degree**.

**Instrument**

Dimensions (Length x Width x Height)

220x120x55mm

Weight 460g (complete with batteries)

Materials ABS, rubber

Display 2x4½ characters plus symbols  
visible area: 52x42mm

**Operating conditions**

Working temperature -5 ... 50°C

-25 ... 65°C

Storage temperature 0 ... 90% RH without condensation

**IP66**

**Power**

Batteries

3 batteries 1.5V type AA

Autonomy (only batteries) 100 hours with 1800mAh alkaline batteries

Mains (cod. SWD10) Output mains adapter 100-240Vac/ 12Vdc-1A

**Security of memorized data**

Unlimited

**Storage of measured values**

Type

2000 pages of 18 samples each

Quantity

36,000 sets of measures made up of [ $\chi$  -  $\Omega$  or TDS or NaCl] and [°C- °F]

**Selectable storage interval**

1s, 5s, 10s, 15s, 30s, 1min, 2min, 5min, 10min, 15min, 20min, 30min and 1hour

**Time**

Date and hour

Schedule in real time

Accuracy

1min/month max drift

**Serial interface RS232C**

Type

RS232C electrically isolated

Can be set from 1200 to 38400 baud

8

None

1

Xon/Xoff

Max 15m

immediate or 1s, 5s, 10s, 15s, 30s, 1min, 2min, 5min, 10min, 15min, 20min, 30min and 1hour

**USB Interface**

Type

1.1 - 2.0 electrically isolated

**Common connections to all models**

Serial interface and USB

8-pole MiniDin connector

Mains adapter (cod. SWD10)

2-pole connector (positive at centre) 12Vdc/1A

**Measurement connections**

Input conductivity

8-pole male DIN45326 connector

Input for temperature probes

8-pole male DIN45326 connector

complete with TP47 modules

**Measurement of conductivity by instrument**

Measurement range (Kcell=0.01)

**Resolution**

0.000...1.999µS/cm

0.001µS/cm

Measurement range (Kcell=0.1)

0.00...19.99µS/cm

0.01µS/cm

Measurement range (Kcell=1)

0.0...199.9µS/cm

0.1µS/cm

200...1999µS/cm

1µS/cm

2.00...19.99mS/cm

0.01mS/cm

20.0...199.9mS/cm

0.1mS/cm

200...1999mS/cm

1mS/cm

±0.5% ±1digit

Measurement range (Kcell=10).

Accuracy (conductivity)

N.C.

Vdc in

N.C.

8-pole Mini DIN

8-pole DIN 45326



<i>Measurement of resistivity by instrument</i>		<i>Resolution</i>	
Measurement range (Kcell=0.01)	Up to 1GΩ·cm	(*)	
Measurement range (Kcell=0.1)	Up to 100MΩ·cm	(*)	
Measurement range (Kcell=1)	5.0...199.9Ω·cm	0.1Ω·cm	
	200...999Ω·cm	1Ω·cm	
	1.00k...19.99kΩ·cm	0.01kΩ·cm	
	20.0k...99.9kΩ·cm	0.1kΩ·cm	
	100k...999kΩ·cm	1kΩ·cm	
	1...10MΩ·cm	1MΩ·cm	
Measurement range (Kcell=10)	0.5...5.0Ω·cm	0.1Ω·cm	
Accuracy (resistivity)	±0.5% ±1digit		
<i>Measurement of total dissolved solids (with coefficient X/TDS=0.5)</i>			
Measurement range (Kcell=0.01)	0.00...1.999mg/l	0.005mg/l	
Measurement range (Kcell=0.1)	0.00...19.99mg/l	0.05mg/l	
Measurement range (Kcell=1)	0.0...199.9 mg/l	0.5 mg/l	
	200...1999 mg/l	1 mg/l	
	2.00...19.99 g/l	0.01 g/l	
	20.0...99.9 g/l	0.1 g/l	
Measurement range (Kcell=10)	100...999 g/l	1 g/l	
Accuracy (total dissolved solids)	±0.5% ±1digit		
<i>Measurement of salinity</i>			
Measurement range	0.000...1.999g/l	1mg/l	
	2.00...19.99g/l	10mg/l	
Accuracy (salinity)	20.0...199.9g/l	0.1g/l	
<i>Temperature measurement by instrument</i>			
Measurement range Pt100	-50...+200°C		
Measurement range Pt1000	-50...+200°C		
Resolution	0.1°C		
Accuracy	±0.25°C		
Drift after 1 year	0.1°C/year		
<i>Automatic/manual temperature compensation</i>	0...100°C with $\alpha_T = 0.00...4.00\%/\text{°C}$		
<i>Reference temperature</i>	20°C or 25°C selectable from menu		
<i>Conversion factor X/TDS</i>	0.4...0.8		
<i>Cell constant K (cm<sup>-1</sup>)</i>	0.01 - 0.1 - 0.7 - 1.0 - 10.0		
<i>Standard solutions automatically detected (@25°C)</i>	147µS/cm 1413µS/cm 12880µS/cm 111800µS/cm		

(\*) The resistivity measurement is obtained from the reciprocal of conductivity measurement. Close to the bottom of the scale, the indication of resistivity appears like reported in the table below:

K cell = 0.01 cm <sup>-1</sup>		K cell = 0.1 cm <sup>-1</sup>	
Conductivity (µS/cm)	Resistivity (MΩ·cm)	Conductivity (µS/cm)	Resistivity (MΩ·cm)
0.001 µS/cm	1000 MΩ·cm	0.01 µS/cm	100 MΩ·cm
0.002 µS/cm	500 MΩ·cm	0.02 µS/cm	50 MΩ·cm
0.003 µS/cm	333 MΩ·cm	0.03 µS/cm	33 MΩ·cm
0.004 µS/cm	250 MΩ·cm	0.04 µS/cm	25 MΩ·cm

#### ORDERING CODES

**HD3406.2:** The kit is composed of: instrument HD3406.2 **datalogger**, for measurement of conductivity - resistivity - TDS - salinity - temperature, 3 1.5V alkaline batteries, operating manual and **DeltaLog9 version 2.0**.

**Conductivity probes, temperature probes, standard reference solutions, cables for data download to PC or printer have to be ordered separately.**

#### Accessories

**HD2110CSNM:** 8-pole connection cable Mini Din - Sub D 9-pole female for RS232C, for connection to PC without USB input.

**HD2101/USB:** Connection cable USB 2.0 connector type A - 8-pole Mini Din for connection to PC with USB input.

**SWD10:** Stabilized power supply at 100-240Vac/12Vdc-1A mains voltage.

**HD40.1:** Portable, serial input, 24 column thermal printer, 57mm paper width.

**HD22.2:** Laboratory electrode holder composed of basis plate with incorporated magnetic stirrer, staff and replaceable electrode holder. Height max. 380mm.

**HD22.3:** Laboratory electrode holder with metal basis plate. Flexible electrode holder for free positioning. For Ø 12mm probes.

**TP47:** Connector for Pt100 4-wire and Pt1000 2-wire probes without SICRAM module.

#### Combined conductivity and temperature probes

**SP06T:** Combined conductivity and temperature 4-electrode cell in Platinum, body in Pocan. Cell constant K = 0.7. Measurement range 5µS/cm...200mS/cm, 0...90°C. Max. working pressure 5bar.

**SPT401.001:** Combined conductivity and temperature 2-electrode cell in stainless steel AISI 316. Cell constant K = 0.01. Measurement range 0.04µS/cm...20µS/cm, 0...120°C. **Measurement in closed-cell.** Max. working pressure 5bar.

**SPT01G:** Combined conductivity and temperature 2-electrode Platinum-wire cell, body in glass. Cell constant K = 0.1. Measurement range 0.1µS/cm...500µS/cm, 0...80°C. Max. working pressure 5bar.

**SPT1G:** Combined conductivity and temperature 2-electrode Platinum-wire cell, body in glass. Cell constant K = 1. Measurement range 10µS/cm...10mS/cm, 0...80°C. Max. working pressure 5bar.

**SPT10G:** Combined conductivity and temperature 2-electrode Platinum-wire cell, body in glass. Cell constant K = 10. Measurement range 500µS/cm...200mS/cm, 0...80°C. Max. working pressure 5bar.

#### Standard conductivity calibration solutions

**HD8747:** Standard calibration solution 0.001mol/l equal to 147µS/cm @25°C - 200cc.

**HD8714:** Standard calibration solution 0.01mol/l equal to 1413µS/cm @25°C - 200cc.

**HD8712:** Standard calibration solution 0.1mol/l equal to 12880µS/cm @25°C - 200cc.

**HD87111:** Standard calibration solution 1mol/l equal to 111800µS/cm @25°C - 200cc.

#### Temperature probes complete with SICRAM module

**TP472I:** Wire wound Pt100 sensor, immersion probe. Stem Ø 3 mm, length 300 mm. Cable length 2 m.

**TP472I.0:** Thin film Pt100 sensor, immersion probe. Stem Ø 3 mm, length 230 mm. Cable length 2 m.

**TP473P.I:** Wire wound Pt100 sensor, penetration probe. Stem Ø 4mm, length 150 mm. Cable length 2 m.

**TP473P.0:** Thin film Pt100 sensor, penetration probe. Stem Ø 4mm, length 150 mm. Cable length 2 m.

**TP474C.I:** Wire wound Pt100 sensor, contact probe. Stem Ø 4mm, length 230mm, contact surface Ø 5mm. Cable length 2 m.

**TP474C.0:** Thin film Pt100 sensor, contact probe. Stem Ø 4mm, length 230mm, contact surface Ø 5mm. Cable length 2 m.

**TP475A.0:** Thin film Pt100 sensor, air probe. Stem Ø 4mm, length 230mm. Cable length 2 m.

**TP472I.5:** Thin film Pt100 sensor, penetration probe. Stem Ø 6mm, length 500 mm. Cable length 2 m.

**TP472I.10:** Thin film Pt100 sensor, penetration probe. Stem Ø 6mm, length 1000mm. Cable length 2 m.

**TP49A.0:** Thin film Pt100 sensor, immersion probe. Stem Ø 2,7mm, length 150mm. Cable length 2 m. Aluminium handle

**TP49AC.0:** Thin film Pt100 sensor, contact probe. Stem Ø 4mm, length 150mm. Cable length 2 m. Aluminium handle

**TP49AP.0:** Thin film Pt100 sensor, penetration probe. Stem Ø 2,7mm, length 150mm. Cable length 2 m. Aluminium handle

**TP875.I:** Wire wound Pt100 sensor, 150mm diameter globe-thermometer equipped with handle. Cable length 2 m.

**TP876.I:** Wire wound Pt100 sensor, 50mm diameter globe-thermometer equipped with handle. Cable length 2 m.

**TP87.0:** Thin film Pt100 sensor, immersion probe. Stem Ø 3 mm, length 70 mm. Cable length 2 m.

**TP878.0:** Thin film Pt100 sensor, contact probe for solar panels. Cable length 2 m.

**TP878.1.0:** Thin film Pt100 sensor, contact probe for solar panels. Cable length 5 m.

**TP879.0:** Thin film Pt100 sensor, penetration probe for compost. Stem Ø 8 mm, length 1000 mm. Cable length 2 m.

#### Temperature probes without SICRAM module

**TP47.100.0:** Thin film Pt100 sensor, immersion probe. Stem Ø 3mm, length 230mm. Connection cable 4 wires with connector, length 2 m.

**TP47.1000.0:** Thin film Pt1000 sensor, immersion probe. Probe's stem Ø 3mm, length 230mm. Connection cable 4 wires with connector, length 2 m.

**TP47:** Connector for Pt100 4-wire and Pt1000 2-wire probes without SICRAM module.

**TP87.100.0:** Thin film Pt100 sensor, immersion probe. Stem Ø 3mm, length 70mm. 4-wires connection cable with connector, length 1 m.

**TP87.1000.0:** Thin film Pt1000 sensor, immersion probe. Stem Ø 3mm, length 70mm. 2-wires connection cable with connector, length 1 m.



**Архангельск** (8182)63-90-72  
**Астана** (7172)727-132  
**Астрахань** (8512)99-46-04  
**Барнаул** (3852)73-04-60  
**Белгород** (4722)40-23-64  
**Брянск** (4832)59-03-52  
**Владивосток** (423)249-28-31  
**Волгоград** (844)278-03-48  
**Вологда** (8172)26-41-59  
**Воронеж** (473)204-51-73  
**Екатеринбург** (343)384-55-89  
**Иваново** (4932)77-34-06

**Ижевск** (3412)26-03-58  
**Иркутск** (395)279-98-46  
**Казань** (843)206-01-48  
**Калининград** (4012)72-03-81  
**Калуга** (4842)92-23-67  
**Кемерово** (3842)65-04-62  
**Киров** (8332)68-02-04  
**Краснодар** (861)203-40-90  
**Красноярск** (391)204-63-61  
**Курск** (4712)77-13-04  
**Липецк** (4742)52-20-81  
**Киргизия** (996)312-96-26-47

**Магнитогорск** (3519)55-03-13  
**Москва** (495)268-04-70  
**Мурманск** (8152)59-64-93  
**Набережные Челны** (8552)20-53-41  
**Нижний Новгород** (831)429-08-12  
**Новокузнецк** (3843)20-46-81  
**Новосибирск** (383)227-86-73  
**Омск** (3812)21-46-40  
**Орел** (4862)44-53-42  
**Оренбург** (3532)37-68-04  
**Пенза** (8412)22-31-16  
**Казахстан** (772)734-952-31

**Пермь** (342)205-81-47  
**Ростов-на-Дону** (863)308-18-15  
**Рязань** (4912)46-61-64  
**Самара** (846)206-03-16  
**Санкт-Петербург** (812)309-46-40  
**Саратов** (845)249-38-78  
**Севастополь** (8692)22-31-93  
**Симферополь** (3652)67-13-56  
**Смоленск** (4812)29-41-54  
**Сочи** (862)225-72-31  
**Ставрополь** (8652)20-65-13  
**Таджикистан** (992)427-82-92-69

**Сургут** (3462)77-98-35  
**Тверь** (4822)63-31-35  
**Томск** (3822)98-41-53  
**Тула** (4872)74-02-29  
**Тюмень** (3452)66-21-18  
**Ульяновск** (8422)24-23-59  
**Уфа** (347)229-48-12  
**Хабаровск** (4212)92-98-04  
**Челябинск** (351)202-03-61  
**Череповец** (8202)49-02-64  
**Ярославль** (4852)69-52-93