

Калибраторы для рН-метров и ОВП-метров DELTA OHM HD9609

Технические характеристики

Архангельск (8182)63-90-72	Ижевск (3412)26-03-58	Магнитогорск (3519)55-03-13	Пермь (342)205-81-47	Сургут (3462)77-98-35
Астана (7172)727-132	Иркутск (395)279-98-46	Москва (495)268-04-70	Ростов-на-Дону (863)308-18-15	Тверь (4822)63-31-35
Астрахань (8512)99-46-04	Казань (843)206-01-48	Мурманск (8152)59-64-93	Рязань (4912)46-61-64	Томск (3822)98-41-53
Барнаул (3852)73-04-60	Калининград (4012)72-03-81	Набережные Челны (8552)20-53-41	Самара (846)206-03-16	Тула (4872)74-02-29
Белгород (4722)40-23-64	Калуга (4842)92-23-67	Нижний Новгород (831)429-08-12	Санкт-Петербург (812)309-46-40	Тюмень (3452)66-21-18
Брянск (4832)59-03-52	Кемерово (3842)65-04-62	Новокузнецк (3843)20-46-81	Саратов (845)249-38-78	Ульяновск (8422)24-23-59
Владивосток (423)249-28-31	Киров (8332)68-02-04	Новосибирск (383)227-86-73	Севастополь (8692)22-31-93	Уфа (347)229-48-12
Волгоград (844)278-03-48	Краснодар (861)203-40-90	Омск (3812)21-46-40	Симферополь (3652)67-13-56	Хабаровск (4212)92-98-04
Вологда (8172)26-41-59	Красноярск (391)204-63-61	Орел (4862)44-53-42	Смоленск (4812)29-41-54	Челябинск (351)202-03-61
Воронеж (473)204-51-73	Курск (4712)77-13-04	Оренбург (3532)37-68-04	Сочи (862)225-72-31	Череповец (8202)49-02-64
Екатеринбург (343)384-55-89	Липецк (4742)52-20-81	Пенза (8412)22-31-16	Ставрополь (8652)20-65-13	Ярославль (4852)69-52-93
Иваново (4932)77-34-06	Киргизия (996)312-96-26-47	Казахстан (772)734-952-31	Таджикистан (992)427-82-92-69	

Единый адрес для всех регионов: dmh@nt-rt.ru || www.deltaohm.nt-rt.ru

HD 9609



TECHNICAL CHARACTERISTICS

pH simulation:	0÷14 pH
pH resolution:	0.1 pH
pH accuracy 20±25°C:	0.002 pH
Thermal drift:	±0.0005 pH/°C from -5°C to 20°C and from 25°C to 50°
mV simulation:	±1999 mV
mV resolution:	1 mV
mV accuracy:	±100 µV
Thermal drift mV scale:	-199.9 ... +199.9: ±0.01 mV/°C from -5 to 20°C and from 25 to 50°C
Thermal drift mV scale:	-1999 ... +1999: ±0.05 mV/°C from -5 to 20°C and from 25 to 50°C
Noise 0÷10 Hz:	1µV peak/peak
Simulation of temperature compensation:	-20 to 150°C (-4 to 302°F)
Output impedance:	100 kΩ 1%, 1GΩ 5% (no leading load capacity)
Display:	LCD 2 lines, 3 ½ digits. Figure height approx. 12.5 mm.
Symbols:	pH, mV, °C, °F, HI imp., LO imp., 0.1 pH, 1 pH, 1 mV, 10 mV
Signals:	LOU, ER1, CAL
Working temperature:	-5 to 50°C (23 to 122°F)
Power supply:	9 Vdc alkaline battery. Low battery indication.
Consumption (instrument only):	5 mA lit up, 20 µA turned off
Autonomy:	about 200 hours
Dimensions:	187 x 72 x 38 mm.
Weight:	300 gr

ORDER CODES

HD 9609: The kit is made of: instrument HD 9609, adapter cables CP 9509BNC, CP 9509 T, carrying case

CP 9509BNC: Adapter cable L = 1 mt, male BNC connector on both ends

CP 9509 T: Adapter cable L = 1 mt, BNC connector on only one end

CP 9509 S7: Adapter cable L = 1 mt, BNC wall connector one end, S7 male connector on the other end.

HD9609

pH AND mV SIMULATOR

GENERAL CHARACTERISTICS

The simulator **HD 609** is a portable instrument for checking and calibrating pH and mV measuring instruments. The characteristics of this instrument satisfy any checking and calibrating requirements for both portable and panel-mounted instruments; it can be used in laboratories, in industry or for check out on field.

Despite its many functions, the instrument is simple to be used: a large display, with dual indication, and a series of symbols allow it to be used even by unskilled personnel.

The HD9609 outputs on channel A the simulation of signals of an electrode for measuring pH, ORP, ISFET, in the range:

- 0 to 14 pH, with resolution 0.10 pH;
- ±1999 mV, with resolution 1 mV.

It is possible to choose between two output impedance values:

- 100 kΩ, low impedance;
- 1 GΩ, high impedance.

The simulation of the temperature compensation electrode is programmed manually in the range from -20°C to +150°C, while the temperature is measured in Celsius or Fahrenheit degrees.

The pH simulation values can be manually set as desired, in steps of 0.1 or 1 pH. The mV simulation values can be manually set as desired, in steps of 1 or 10 mV.

The HD9609 is powered by an ordinary 9Vdc alkaline battery.

The electronics are housed in a sturdy ABS case with ergonomic lines.

In designing and making the instrument, each detail has been assessed and selected in order to provide an instrument with high performance and excellent long-term measurement stability.



Архангельск (8182)63-90-72	Ижевск (3412)26-03-58	Магнитогорск (3519)55-03-13	Пермь (342)205-81-47	Сургут (3462)77-98-35
Астана (7172)727-132	Иркутск (395)279-98-46	Москва (495)268-04-70	Ростов-на-Дону (863)308-18-15	Тверь (4822)63-31-35
Астрахань (8512)99-46-04	Казань (843)206-01-48	Мурманск (8152)59-64-93	Рязань (4912)46-61-64	Томск (3822)98-41-53
Барнаул (3852)73-04-60	Калининград (4012)72-03-81	Набережные Челны (8552)20-53-41	Самара (846)206-03-16	Тула (4872)74-02-29
Белгород (4722)40-23-64	Калуга (4842)92-23-67	Нижний Новгород (831)429-08-12	Санкт-Петербург (812)309-46-40	Тюмень (3452)66-21-18
Брянск (4832)59-03-52	Кемерово (3842)65-04-62	Новокузнецк (3843)20-46-81	Саратов (845)249-38-78	Ульяновск (8422)24-23-59
Владивосток (423)249-28-31	Киров (8332)68-02-04	Новосибирск (383)227-86-73	Севастополь (8692)22-31-93	Уфа (347)229-48-12
Волгоград (844)278-03-48	Краснодар (861)203-40-90	Омск (3812)21-46-40	Симферополь (3652)67-13-56	Хабаровск (4212)92-98-04
Вологда (8172)26-41-59	Красноярск (391)204-63-61	Орел (4862)44-53-42	Смоленск (4812)29-41-54	Челябинск (351)202-03-61
Воронеж (473)204-51-73	Курск (4712)77-13-04	Оренбург (3532)37-68-04	Сочи (862)225-72-31	Череповец (8202)49-02-64
Екатеринбург (343)384-55-89	Липецк (4742)52-20-81	Пенза (8412)22-31-16	Ставрополь (8652)20-65-13	Ярославль (4852)69-52-93
Иваново (4932)77-34-06	Киргизия (996)312-96-26-47	Казахстан (772)734-952-31	Таджикистан (992)427-82-92-69	

Единый адрес для всех регионов: dmh@nt-rt.ru || www.deltaohm.nt-rt.ru